Warning: Refer to current foreign charts and flight information publications for information while foreign airspace is closed.

L-36 HIGH ENROUTE CHARTS

L-35 FAIRFIELD A-D ABCD +7 NM

UNITED STATES GOVERNMENT FLIGHT INFORMATION PUBLICATION

IFR ENROUTE LOW ALTITUDE - U.S.

For use up to but not including 18,000' MSL

HORIZONTAL DATUM: NORTH AMERICAN DATUM OF 1983

EFFECTIVE 0901Z **29 JUL 2010**

TO 0901Z **23 SEP 2010**

Consult NOTAMs for latest information

PUBLISHED UNDER THE AUTHORITY OF THE SECRETARY OF TRANSPORTATION. DEPARTMENT OF DEFENSE AND DEPARTMENT OF COMMERCE IN NATIONAL AERONAUTICAL CHARTING AND GEODETIC SATISFACTION.

MILITARY TRAINING ROUTES

NUMBER	ALTITUDE RANGE	NUMBER	ALTITUDE RANGE	NUMBER	ALTITUDE RANGE
IR-001	1500 TO 10000	IR-706	500 AGL TO 10000	VR-171	100 AGL TO 10000
IR-131	5000 TO 10000	IR-719	5000 TO 18000	VR-172	100 AGL TO 10000
IR-151	300 AGL TO 4000	IR-720	5000 TO 8000	VR-173	100 AGL TO 6000 AGL
IR-152	5000 TO 10000	IR-721	300 AGL TO 5000	VR-183	100 AGL TO 6000
IR-181	9500 TO 10000	IR-740	SURFACE TO 6000	VR-184	100 AGL TO 6000 AGL
IR-182	9500 TO 10000	IR-743	SURFACE TO 9000	VR-185	100 AGL TO 5000
IR-183	9500 TO 10000	VR-42	100 AGL TO 10000	VR-186	500 AGL TO 8000
IR-184	9500 TO 10000	VR-43	100 AGL TO 10000	VR-187	500 AGL TO 8000
IR-717	5000 TO 8000	VR-45	100 AGL TO 10000	VR-190	500 AGL TO 8000

UNITED STATES 29 JUL 2010



ATTENTION

THIS CHART CONTAINS OFF ROUTE OBSTRUCTION CLEARANCE ALTITUDES (OROCA).

The off route obstruction clearance altitude shown in quadrangles bounded by tinted lines of latitude and longitude are represented in THOUSANDS and HUNDREDS of feet above mean sea level. The OROCA is based on information available concerning the highest known feature in each quadrangle including terrain and obstructions. OROCA provides for clearance with a 1000 foot buffer in designated mountainous areas and a 2000 foot buffer in all other areas. It does not provide for en route navigation aid coverage, for areas in Mexico and the Caribbean which are located outside of the U.S. ADC, OROCA provides obstruction clearance with a 2000 foot buffer. This altitude is provided for obstruction clearance only and may not provide for adequate navigation signal or communication coverage, and would not be consistent with altitudes assigned by Air Traffic Control.

Example: 12,500 feet

12[5]

CORRECTIONS, COMMENTS, AND/OR PROCUREMENT

FOR RECOMMENDATIONS REGARDING FORMAT AND CONTENT (CONTACT):

FAA, Aeronautical Information Services, AJR-321
800 Independence Ave., S.W.,
Washington, DC 20591
Online at 1866.USA.1836.gov
Email: 9-AWA-AOR-AIS-Feedback@faa.gov
Telephone: 1-866-295-8626

FOR CHARTING ERRORS (CONTACT:

FAA, National Aeronautical Navigation Services, ATO-W
Aeronautical Information Group
1305 East-West Highway
Silver Spring, MD 20910-3281
Telephone 1-800-638-2497
Email: 9-amc-chartfeedback@faa.gov

Property owners and developers WHO are concerned on our web site at http://ARCHIVA.FAA.GOV. See the FAQs prior to contact via toll free number or email.

FOR PROCUREMENT (CONTACT):

FAA, National Aeronautical Navigation Services
Distribution Team, ATO-W
10201 Good Luck Road
Lanham, MD 20706-4503
Online at http://ARCHIVA.FAA.GOV
Email: 9-AMC-ChartsMail@faa.gov
Telephone: 301-497-8237 Fax: 301-436-6829
or any authorized FAA agent.

MILITARY:

For Corrections see Chapter 11 of General Planning (GP). For Procurement refer to DOD Catalog of Aeronautical Charts and Flight Information Publications.

Published by the
U.S. Department of Transportation
Federal Aviation Administration
Aeronautical Services
http://ARCHIVA.FAA.GOV

FAA Product ID: ELUBSS

NSN 7641015487585

ISSN ENR90USLCHT3S

ISBN 10210